



WEVER & DUCRÉ
LIGHTING

CENO 2.0

166261B3

Project
Type
Notes
Quantity
Date

GENERAL

Ceiling
 Recessed
 Jet Black
 IP20
 Interior
 895 lm
 9005^a

LED

2700 K
 CRI 90
 L70 / 50000 h
 3-step binning

OPTICAL

Flood
 Beam angle 34°

PHYSICAL

Length 154 mm
 Width 40 mm
 Height 30 mm
 0.26 kg
 Tilt min 90°
 Tilt max 90°
 Rotation 350°


ELECTRICAL

excl. power supply
 18 V
 Total connected power 8.3 W
 LED Inset 6.2 W
 700 mA
 PC3
 Safety distance 0.3 m


CUTOUT

Length 145 mm
 Width 32 mm
 Min. ceiling thickness 8 mm
 Max. ceiling thickness 25 mm
 Recessed depth 60 mm

^a RAL Palette colors may deviate slightly due to production conditions.



LIGHT DISTRIBUTION





WEVER & DUCRÉ
LIGHTING

CENO 2.0

166261B3

CONE DIAGRAM

flood 35° 700mA

h (m)	EO ² (lx)	ø (m)
1	2250	0.63
2	564	1.25
3	251	1.88
4	141	2.50
5	90	3.13

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.92	0.88	0.83	0.79	0.76
LSF	1	1	1	1	1

MF	LMF × RSMF × LLMF × LSF	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

ELECTRICAL

Power Supply 700mA

TYPE	L · W · H (MM)	VOLTAGE	ORDERCODE
14W 10-20V phase-cut dim 5-100%	102·51·30		9 0 2 2 5 5 0 1
15W dim	122·41·23	12-20V	9 0 2 2 5 5 0 2
20W 3-28V DALI 0-100%	111·52·22	3-28V	9 0 2 4 5 6 0 2

OPTICAL

Honeycomb

TYPE	COLOUR	(MM)	ORDERCODE
CENO PIRRO BLIEK PETIT	Pure White	29	9 0 0 5 1 1 3 0
CENO PIRRO BLIEK PETIT	Signal Black	29	9 0 0 5 1 1 3 1



e29