



WEVER & DUCRÉ
LIGHTING

MATCH 1.0

190151W5

Project

Type

Notes

Quantity

Date

GENERAL

Ceiling

Recessed

Tilt max 90°

Rotation 350°

White Matt

Below IP20

Interior

600 lm

LED

3000 K

OPTICAL

Beam angle 30°

ELECTRICAL

excl. power supply

18 V

LED Inset 6 W

350 mA

Class 3

Safety distance 0.3 m

PHYSICAL

Diameter 26 mm

Height 117 mm

0.14 kg

wire springs

CUTOUT

Diameter 45-47 mm


Min. ceiling thickness 4 mm

Max. ceiling thickness 26 mm

Recessed depth 85 mm



Ceiling recessed spotlight made from die-cast aluminium with round base; installation without tools using wire springs; suitable for ceiling thickness of 4-26 mm; recessed depth 85 mm; with COB (Chip on Board) technology for maximum efficiency; light colour 3000 K; beam angle 30°; spotlight head 350° rotatable and 90° tiltable; degree of protection IP20; PC3; driver not included; light source replaceable by an authorized professional;





WEVER & DUCRÉ
LIGHTING

MATCH 1.0

190151W5

ELECTRICAL

Driver

TYPE	L · W · H (MM)	VOLTAGE	ORDERCODE
10W 350mA 12-28V	102·38·21	12 - 28V	9 0 2 2 3 4 0 2
10W 350mA 5-29V	124·31·21	2.5 - 26V	9 0 2 4 3 4 0 1