



**WEVER & DUCRÉ**  
LIGHTING

# MATCH 2.0

190251W5

Project	.....
Type	.....
Notes	.....
Quantity	.....
Date	.....

## GENERAL

Ceiling	.....
Recessed	.....
Tilt max 90°	.....
Rotation 350°	.....
White Matt	.....
Below IP20	.....
Interior	.....
1200 lm	.....

## LED

3000 K	.....
--------	-------

## OPTICAL

Beam angle 25°	.....
----------------	-------

## ELECTRICAL


excl. power supply	.....
18 V	.....
LED Inset 12 W	.....
700 mA	.....
Class 3	.....
Safety distance 0.3 m	.....

## PHYSICAL


Length 26 mm	.....
Width 125 mm	.....
Height 117 mm	.....
0.27 kg	.....
wire springs	.....

## CUTOUT

Length 105 mm	.....
Width 30 mm	.....
Min. ceiling thickness 4 mm	.....
Max. ceiling thickness 26 mm	.....
Recessed depth 60 mm	.....



Ceiling recessed luminaire with 2 spotlights; made from die-cast aluminium with base; installation without tools using wire springs; suitable for ceiling thickness of 4-26 mm; recessed depth 60 mm; with COB (Chip on Board) technology for maximum efficiency; light colour 3000 K; beam angle 25°; spotlight head 350° rotatable and 90° tiltable; degree of protection IP20; PC3; driver not included; light source replaceable by an authorized professional;





WEVER & DUCRÉ  
LIGHTING

# MATCH 2.0

190251W5

## ELECTRICAL

### Driver

TYPE	L · W · H (MM)	VOLTAGE	ORDERCODE
15W   700mA   12-20V	122·41·23	12 - 20V	9 0 2 2 5 5 0 2
28W   700mA   3-40V	136·42,5·24	9 - 40V	9 0 2 4 5 8 0 1