



PROJECT _____

TYPE _____

NOTES _____

QUANTITY _____

DATE _____



Disc shaped wall surface luminaire ; surface White Marble; No matching RAL; PCB 3-step binning; phase-cut dim; light colour 2700 K; ≤ 3 SDCM (initial MacAdam); CRI ≥ 90 ; 220 - 240 V; degree of protection IP20; Class 2; light source replaceable by Wever & Ducré or by a professional with explicit authorization;

LUMINAIRE

- Wall _____
- Surface _____
- White Marble _____
- No matching RAL _____
- IP20 _____
- Interior _____
- 610 lm _____

LED Module

- 2700 K _____
- CRI ≥ 90 _____
- L80 / 70000 h _____
- ≤ 3 SDCM (initial MacAdam) _____

Optical

- Indirect _____
- CIE flux code: 0 2 28 22 100 _____



Electrical

- phase-cut dim _____
- 220 - 240 V _____
- system 8.5 W _____
- Class II _____
- Standard _____

Physical

- diameter 190 mm _____
- height 43 mm _____
- 1.24 kg _____

LIGHT DISTRIBUTION





Maintenance Factor

Operating Time [h]	10.000	20.000	30.000	40.000	50.000
LLMF	0.98	0.95	0.92	0.89	0.86
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Factor

^aAccording to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.