



WEVER & DUCRÉ
LIGHTING

RAY WALL mini 1.0

300220G0

Project

Type

Notes

Quantity

Date

GENERAL

Wall
Surface
Gold
IP20
Interior
445^a to 450^b lm

LED

Lamp PAR16
PAR16
Socket GU10
max. 12 W
L70 / 50000 h

OPTICAL

Beam angle 48°
UGR < 19
65° < 3000 cd/m²



PHYSICAL

Diameter 67 mm
Height 115 mm
0.21 kg


ELECTRICAL

100 - 240 V
Total connected power 8.8^b to 8.9^a W
PC1
Safety distance 0.3 m

^a LED 3000K CRI 80 white
^b LED 2700K CRI 80 white



LIGHT DISTRIBUTION



[300220G0] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BVBA apply.
© Wever & Ducré BVBA · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com



WEVER & DUCRÉ
LIGHTING

RAY

WALL mini 1.0

300220G0

LED LAMPS

PAR16 LED Lamp

TYPE	COLOUR	Ø·H (MM)	ORDERCODE
2700K >90 CRI GU10	Jet Black	∅50·58	9 0 1 2 2 8 B 3
3000K >90 CRI GU10	Jet Black	∅50·58	9 0 1 2 2 8 B 5
2700K >80 CRI GU10	Signal White	∅50·58	9 0 1 2 2 8 W 2
2700K >90 CRI GU10	Signal White	∅50·58	9 0 1 2 2 8 W 3
3000K >80 CRI GU10	Signal White	∅50·58	9 0 1 2 2 8 W 4