




PROJECT _____

TYPE _____


NOTES _____

QUANTITY _____

DATE _____



Wall surface luminaire made from aluminium; surface Black Matt; powder coated, matt texture; RAL 9011; opal PMMA diffuser; PCB 3-step binning; phase-cut dim; light colour 2700 K; ≤ 3 SDCM (initial MacAdam); CRI ≥ 90 ; CRI (Colour Rendering Index) ≥ 90 ; 220 - 240 V; degree of protection IP20; Class 1; driver included; light source replaceable by Wever & Ducré or by a professional with explicit authorization; control gear replaceable by end-user;



LUMINAIRE

Wall _____

Surface _____

Black Matt _____

RAL 9011 ^a _____

IP20 _____

Interior _____

450 lm _____

LED Module

2700 K _____

CRI ≥ 90 _____

L80 / 50000h _____

≤ 3 SDCM (initial MacAdam) _____

600 lm _____

164 lm/W ^b _____

Optical

Opal _____

CIE flux code: 11 35 66 50 100 _____

Electrical

phase-cut dim _____

220 - 240 V _____

system 5.2 W _____

Class I _____

Standard _____


Physical

diameter 9 mm _____

height 623 mm _____

0.15 kg _____

LIGHT DISTRIBUTION



^a Colour may deviate slightly due to production conditions
^b Without electrical and optical losses



Maintenance Factor

Operating Time [h]	10.000	20.000	30.000	40.000	50.000
LLMF	0.98	0.97	0.95	0.93	0.92
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Factor

^aAccording to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

MOUNTING ACCESSORIES

Wall-/Base-Spacer Type	Colour	Voltage	L·W·H (MM)	Item number
FINLIN	Black		45·26·18	900195B0